

FORKOLL®

ADESIVI E COLLANTI PER L'EDILIZIA
ADHESIVES AND GLUES FOR CONSTRUCTION

Strada Prov. 42 - Km. 1
73040 COLLEPASSO (LE)
Tel. +39 0833 595333 • Fax +39 0833 595531
www.forkoll.it - info@forkoll.it

KLEBSTOFF FÜR FLIESEN UND STEINE
FÜR INNENRÄUME

KLEBESTOFF

SUPERBOND F5



type of product:

hydraulic ultra rapid-setting adhesive powder.

characteristics:

high bonding strength and thixotropy, easy to apply, non-toxic, frost resistant. Excellent workability.

specifications:

coverings must be applied with **Forkoll Superbond F5** hydraulic ultra rapid-setting adhesive powder.

alternative products:

Extrabond F15 - Extraflex B2



PACKAGING: 25 Kg paper bags on 1500 Kg pallet

colour	white and grey
water in the mix	30%
specific weight	1,50 g/cm ³
pH	12,5
adjustability time	45 min
tensile strength after 28 days	1,1 N/mm ²
compressive strength after 28 days	1,1 N/mm ²
set to light foot traffic	after 24 hours
wall grouting	after 24 hours
floor grouting	after 48 hours
complete hardening time	after 28 days
dry solid content	100 %

RANGE OF USE:

ceramic tiles on indoor vertical cementitious supports.
New rough plaster supports.



PREPARING THE SUBSTRATE: the substrates must be free from loose particles, dust, oils, grease and other substances which could compromise compatibility and adhesion.

PREPARING THE MIX: mix 30% clean water with SUPERBOND F5, preferably use a mechanical mixer, until an homogenous paste, free of lumps, is obtained. Wait at least 10 minutes, then the paste is ready for use.

APPLYING THE MIX: it is applied with a notched trowel, like a usual plaster, first use the smooth side of the trowel and then the toothed one.

CONSUMPTION: from 2 to 5 Kg/m² surface depending on the type of substrate.